



HAL
open science

Quantum Observables for Binary, Multi-Valued and Fuzzy Logic: Eigenlogic

Zeno Toffano, François Dubois

► **To cite this version:**

Zeno Toffano, François Dubois. Quantum Observables for Binary, Multi-Valued and Fuzzy Logic: Eigenlogic. 7th Colloquium IQFA-2016, CNRS GDR-3322 on Q. Engineering, Foundations & Applications Ingénierie Quantique, des aspects Fondamentaux aux Applications – IQFA, Nov 2016, Paris, France. hal-01399528

HAL Id: hal-01399528

<https://centralesupelec.hal.science/hal-01399528v1>

Submitted on 19 Nov 2016

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Quantum Observables for Binary, Multi-Valued and Fuzzy Logic : Eigenlogic

Zeno Toffano^{1,2}, François Dubois^{3,4*}

¹*Telecom Dept., CentraleSupélec, Gif-sur-Yvette, France*

²*Laboratoire des Signaux et Systèmes, UMR8506-CNRS, Université Paris-Saclay, France*

³*LMSSC, Conservatoire National des Arts et Métiers, Paris, France*

⁴*Department of Mathematics, University Paris-Sud, Orsay, France*

We propose a linear algebraic method, named Eigenlogic [1], for two-, many-valued and fuzzy logic using observables in Hilbert space. All logical connectives are represented by observables where the truth values correspond to eigenvalues and the atomic input propositional cases, i.e. the “models” of a propositional system, to the respective eigenvectors. In this way propositional logic can be formalized by using combinations of tensored elementary quantum observables. The outcome of a “measurement” of a logical observable will give the truth value of the associated logical proposition, and becomes “interpretable” when applied to vectors of its eigenspace, leading to an original insight into the quantum measurement postulate. Recently the concept of “quantum predicate” has been proposed in [2] leading to similar concepts.

We develop logical observables for binary logic and extend them to many-valued logic.

For binary logic and truth values $\{0, 1\}$ logical observables are commuting projector operators [1].

For truth values $\{+1, -1\}$ the logical observables are isometries formally equivalent to the ones of a composite quantum spin $\frac{1}{2}$ system, these observables are reversible quantum logic gates.

The analogy of many-valued logic with quantum angular momentum is then established using a general algebraic method, based on classical interpolation framework suggested by the finite-element method. Logical observables for three-valued logic are formulated using the orbital angular momentum observable L_z with $\ell = 1$. The representative 3-valued 2-argument logical observables for the ternary threshold logical connectives Min and Max are then explicitly obtained [3].

Also in this approach fuzzy logic arises naturally when considering vectors outside the eigensystem. The fuzzy membership function [4] is obtained by the quantum mean value (Born rule) of the logical projector observable and turns out to be a probability measure. Fuzziness arises because of the quantum superposition of atomic propositional cases, the truth of a proposition being in this case a probabilistic value ranging from completely false to completely true.

This method could be employed for developing algorithms in high-dimensional vector spaces for example in modern semantic theories, such as distributional semantics or in connectionist models of cognition [5]. For practical implementation, due to the exponential growth of the vector space dimension, adapted logical reduction methods must then be used. LSA (Latent Semantic Analysis) algorithms are often used in quantum-like approaches, this was done in [6] using the HAL (Hyperspace Analogue to Language) algorithm.

Our approach is also of interest for quantum computation because several of the observables in Eigenlogic are well-known quantum gates (for example CONTROL-Z) and other ones can be derived by unitary transformations. Ternary-logic quantum gates using qu-trits lead to less complex circuits, our formulation of multi-valued logical observables could help the development of new multi-valued quantum gate architectures.

-
- [1] Toffano, Z. : “Eigenlogic in the spirit of George Boole”, ArXiv :1512.06632 (2015)
- [2] Ying, M.S. : “Foundations of Quantum Programming”, 4.1 “Quantum Predicates”, p.103, Morgan Kaufmann, (2016).
- [3] François Dubois and Zeno Toffano : “Eigenlogic : a Quantum View for Multiple-Valued and Fuzzy Systems”, Quantum Interaction Conference 2016, San Francisco, CA, USA, July 22, 2016; arXiv :1607.03509 (2016)
- [4] Jarosław Pykacz : “Quantum Physics, Fuzzy Sets and Logic” , Springer (2015)
- [5] Busemeyer, J.R., Bruza, P.D. : “Quantum models of cognition and decision”, Cambridge University Press (2012)
- [6] Barros, J., Toffano, Z., Meguebli, Y., Doan, B.L. : “Contextual Query Using Bell Tests”, Springer Lecture Notes in Computer Science, LNCS 8369, 110-121 (2014)

* zeno.toffano@centralesupelec.fr; francois.dubois@cnam.fr

Zeno Toffano ^(1,2), Franois Dubois ^(3,4)

(1) Dep. Telecom, CentraleSup elec, Gif-sur-Yvette, France - (2) Laboratoire de Signaux et Syst emes (L2S - CNRS-UMR8506) - Universit  Paris-Saclay
(3) LMSSC, Conservatoire National des Arts et M tiers, Paris - (4) Department of Mathematics, University Paris-Sud, Orsay, France

Eigenlogic [1]

We propose a linear algebraic model for two- and many-valued logic using families of observables in Hilbert space, the **eigenvalues give the truth values** of logical propositions where the input propositional cases (models for the logical proposition) are represented by the respective eigenvectors.

quantum logical observables → logical connectives

eigenvectors of the observables → models of the propositional system

eigenvalues of the observables → truth values

The **outcome of a measurement on a logical observable** will give the truth value of the associated logical proposition.

In classical logic, predicates are used to describe properties of individuals or systems. A natural idea is that a **quantum predicate** [2] should be a physical observable.

Projector Binary Logical Observables

J. von Neumann considered **projectors as propositions (quantum logic)**.

Two-dimensional rank-1 projector (qubit) $\Pi = |1\rangle\langle 1|$

$$\Pi|1\rangle = 1|1\rangle; \text{ eigenvalue } 1. \quad \Pi|0\rangle = 0|0\rangle; \text{ eigenvalue } 0.$$

Logical observable as a development in Π

Here the elements of the development are the **rank-1 projectors** and the **truth values** $f(0)$ and $f(1)$:

$$F = f(0)\Pi_0 + f(1)\Pi_1 = f(0)(I_d - \Pi) + f(1)\Pi = \begin{pmatrix} f(0) & 0 \\ 0 & f(1) \end{pmatrix}$$

The two-argument logical observables can be developed on the corresponding four rank-1 projectors:

$$F = \begin{pmatrix} f(0,0) & 0 & 0 & 0 \\ 0 & f(0,1) & 0 & 0 \\ 0 & 0 & f(1,0) & 0 \\ 0 & 0 & 0 & f(1,1) \end{pmatrix}$$

The conjunction is here: $F_{AND} = \Pi \otimes \Pi$
All 16 two-argument connectives are derived.

Isometric Binary Logical Observables

There is a linear bijection (isomorphism) from the projector F to a reversible observable G (isometry) using the **Householder transform**:

$$G = I_d - 2F$$

both observables commute and have the same system of eigenvectors.

The eigenvalues that correspond to the truth values, respectively "false" and "true", are now $+1$ and -1 . The seed observable is **Pauli-Z**:

$$Z = I_d - 2\Pi = \begin{pmatrix} +1 & 0 \\ 0 & -1 \end{pmatrix} = \sigma_z$$

The **logical dictators** U and V are expressed as a function of the seed observable Z :

$$U = Z \otimes I_d \quad V = I_d \otimes Z$$

For the isometric observables negation is obtained by multiplying by -1 .

The exclusive disjunction (XOR): $G_{XOR} = Z \otimes Z$

The logical conjunction (AND):

$$G_{AND} = \frac{1}{2}(I + Z \otimes I + I \otimes Z - Z \otimes Z) = \begin{pmatrix} +1 & 0 & 0 & 0 \\ 0 & +1 & 0 & 0 \\ 0 & 0 & +1 & 0 \\ 0 & 0 & 0 & -1 \end{pmatrix} = C^Z$$

which is the quantum **Control-Z** gate

Multivalued Eigenlogic

Identification with **quantum orbital angular moment (OAM)**, The z component of the OAM gives the observable L_z :

The eigenvalues, $\{+1, 0, -1\}$, are the logical values:

"false" $F \equiv +1$ "neutral" $N \equiv 0$ "true" $T \equiv -1$

The logical observables can be expressed as spectral decompositions on the rank-1 projectors of the three-dimensional vector space:

$$\Pi_{+1} = \frac{1}{2}A(A+I) \quad \Pi_0 = I - A^2 \quad \Pi_{-1} = \frac{1}{2}A(A-I)$$

We can define the dictators U and V simply by the rule of composition:

$$U = A \otimes I \quad V = I \otimes A \quad U \cdot V = A \otimes A$$

The logical observables are in this case represented by 9x9 matrices.

Tri-Valued Logical Observables : Min and Max

In tri-valued logic, popular connectives are **Min** and **Max**, defined by their tables:

| Min | $U \vee V$ | F | N | T |
|---------------|------------|----|----|----|
| F $\equiv +1$ | +1 | +1 | +1 | +1 |
| N $\equiv 0$ | +1 | +1 | 0 | 0 |
| T $\equiv -1$ | +1 | 0 | 0 | -1 |

| Max | $U \wedge V$ | F | N | T |
|---------------|--------------|----|----|----|
| F $\equiv +1$ | +1 | +1 | 0 | -1 |
| N $\equiv 0$ | 0 | 0 | 0 | -1 |
| T $\equiv -1$ | -1 | -1 | -1 | -1 |

The corresponding logical observables are given function of the dictators:

$$\begin{cases} \text{Min}_{m=3}(U, V) = \frac{1}{2}(U + V + U^2 + V^2 - U \cdot V - U^2 \cdot V^2) \\ \text{Max}_{m=3}(U, V) = \frac{1}{2}(U + V - U^2 - V^2 + U \cdot V + U^2 \cdot V^2) \end{cases}$$

The **total number of logical connectives** for a system of m values and n arguments is the combinatorial number m^{mn} . For a two-argument system taking 3 values the total number of connectives will be 19683.

Fuzzy Logic Interpretation

Fuzzy logic deals with propositions that can lie between "completely true" and "completely false".

When the **quantum state is not an eigenstate of the logical system** one can always express a state vector as a superposition, for example:

$$|\psi\rangle = c_{00}|00\rangle + c_{01}|01\rangle + c_{10}|10\rangle + c_{11}|11\rangle$$

when more than one coefficient is non-zero we are in the case of a **fuzzy proposition**, that can be interpreted as a quantum superposition of propositional models. Mean values are **fuzzy membership functions** μ [3].

Using the Born rule for the state: $|\varphi\rangle = \sin\alpha|0\rangle + e^{i\beta}\cos\alpha|1\rangle$

$$\mu(a) = \langle \varphi | \Pi | \varphi \rangle = \cos\alpha e^{-i\beta} \langle 1 | \langle 1 \rangle \cos\alpha e^{i\beta} | 1 \rangle = \cos^2\alpha$$

For a compound quantum state: $|\psi\rangle = |\varphi_p\rangle \otimes |\varphi_q\rangle$

$$\mu(a) = \langle \psi | \Pi \otimes I | \psi \rangle = p(1-q) + p \cdot q = p, \quad \mu(b) = \langle \psi | I \otimes \Pi | \psi \rangle = q$$

We can give the "measure" of the conjunction, $A \wedge B$, and the disjunction, $A \vee B$ using the seed projector observable:

$$\begin{cases} \mu(a \wedge b) = \langle \psi | \Pi \otimes \Pi | \psi \rangle = p \cdot q = \mu(a) \cdot \mu(b), \\ \mu(a \vee b) = p + q - p \cdot q = \mu(a) + \mu(b) - \mu(a) \cdot \mu(b) \end{cases}$$

Discussion and Potential Applications

- Several observables in Eigenlogic are well-known quantum gates. e.g. C^Z (**Control-Z**) corresponds here to the conjunction logical observable G_{AND} .
- Operational correspondence between **control logic** (Deutsch's paradigm) and **propositional logic**. A goal could be to express the diagonal forms of observables in Eigenlogic as products of known quantum gates.
- Questions of **how could Eigenlogic be used for quantum computing?**: measurements give truth values, but how to reinject them in a circuit?
- Ternary-logic quantum gates using **qu-trits** lead to less complex circuits (e.g. **Adder**). Our formulation of multi-valued logical observables could help the development of new multi-valued quantum gate architectures.
- The **fuzzy membership function** is obtained by the quantum mean value (Born rule) of the logical projector observable.
- This method could be employed for developing **algorithms** in high-dimensional **vector spaces** for example in **modern semantic theories**, such as distributional semantics or in connectionist models of cognition [4].

Acknowledgements: we want to thank the students of CentraleSup elec who worked on this project in 2016: **Patrick Canipe, Hana  Carri , Guillaume Dubert, Benoit Dufumier, Elvire de La Fresnaye, Mathieu Ha-Sum, Philippe Houdebine, Thibault Mantrand, Victoire Marcilhacy, Caroline Pansard, No mie Perrot, Emery Pierson.**

[1] Franois Dubois and Zeno Toffano: "Eigenlogic: a Quantum View for Multiple-Valued and Fuzzy Systems", Quantum Interaction Conference 2016, San Francisco, CA, USA, July 22, 2016; arXiv:1607.03509.
[2] Ying, M.S.: "Foundations of Quantum Programming", 4.1 "Quantum Predicates", p.103, Morgan Kaufmann, (2016).
[3] Jaroslaw Pykacz: "Quantum Physics, Fuzzy Sets and Logic", Springer (2015).
[4] Barros, J., Toffano, Z., Meguebli, Y., Doan, B.L.: "Contextual Query Using Bell Tests", Springer Lecture Notes in Computer Science, LNCS 8369, 110-121 (2014)