



**HAL**  
open science

# Mineral Identification And Characterization: An Integrated Approach To Recover Mineralogical Information From Hyperspectral Images

Ronan Rialland, Rodolphe Marion, V. Carrere, Charles Soussen,  
Jean-Philippe Poli

► **To cite this version:**

Ronan Rialland, Rodolphe Marion, V. Carrere, Charles Soussen, Jean-Philippe Poli. Mineral Identification And Characterization: An Integrated Approach To Recover Mineralogical Information From Hyperspectral Images. 11th EARSeL SIG IS Workshop, Feb 2019, Brno, Czech Republic. , 2019. hal-02861548

**HAL Id: hal-02861548**

**<https://centralesupelec.hal.science/hal-02861548v1>**

Submitted on 9 Jun 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Mineral Identification And Characterization: An Integrated Approach To Recover Mineralogical Information From Hyperspectral Images

Rialland, Ronan<sup>1</sup>; Marion, Rodolphe<sup>1</sup>; Carrère, Véronique<sup>2</sup>; Soussens, Charles<sup>3</sup>; Poli, Jean-Philippe<sup>4</sup>  
<sup>1</sup>Commissariat à l'Énergie Atomique et aux énergies alternatives, CEA/DAM/DIF, F-91297 Arpajon, France;  
<sup>2</sup>UMR-CNRS 6112 - LPG Nantes, Université de Nantes, 2 rue de la Houssinière, BP 92208, 44322 Nantes CEDEX 3, France;  
<sup>3</sup>L2S, CentraleSupélec-CNRS-Université Paris-Sud, Université Paris-Saclay, 91192 Gif-sur-Yvette, France;  
<sup>4</sup>CEA, LIST, Data Analysis and System Intelligence Laboratory, 91191 Gif-sur-Yvette cedex, France;




## Introduction and objectives


- **Integrated and automatic procedure** for mineral mapping from airborne and spaceborne hyperspectral images
- **Mineral reflectance spectra decomposition** in the VNIR/SWIR using EGO model (Exponential Gaussian Optimization)
- **Noise model** evolution for recent spectrometers
- **Identification procedure** from estimated parameters

## AGM (Automatized Gaussian Model) procedure [1]


### AGM flowchart



### EGO model for the VNIR/SWIR [2][3]



### Signal dependent noise model (reflectance)



### Noise estimation (HYNPE [5])

- 1) Signal and noise separation: HYSIME [6]
- 2) Noise parameter initialization: Methods of Moments
- 3) Noise parameter estimation: Maximum likelihood

### EGO model parameter estimation

- 1) Continuum and absorption separation [4]
- 2) Continuum parameters initialization: nonlinear least squares
- 3) Absorptions parameters initialization: continuous wavelet transform [7] + nonlinear least squares
- 4) Joint continuum and absorption parameters estimation: optimal estimation [8] or nonlinear least squares


### Mineral identification and characterization

- 1) Database of EGO model parameters and their variabilities calculated from a database of specific mineral reflectance spectra
- 2) Compare, using a fuzzy logic system [9] and a set of expert rules, the database and the estimated EGO model parameters
- 3) Identification is mainly based on the positions of the absorptions
- 4) Depending on the identified mineral, several properties (composition, grain size, humidity) can be evaluated

## Results

### EGO model validation

- Goals: 1 - EGO and MGM models comparison  
 2 - Asymmetry and saturation evaluation



Sample - Method	Calcite - [11]	Calcite - MGM	Calcite - EGO (without saturation)	Calcite - EGO
Center	2.34 (theory) - 2.335 (measure)	2.31661	2.33516	2.33386
Amplitude	-0.32865	-0.324858	-0.426273	-0.431379
Width	0.09	0.0321666	0.0318745	0.0683448
Asymmetry	= -0.4		0.393188	0.761379
Saturation	/	/	/	-10


  

Sample - Method	Dolomite - [11]	Dolomite - MGM	Dolomite - EGO (without saturation)	Dolomite - EGO
Center	2.32 (theory) - 2.315 (measure)	2.30195	2.31275	2.31306
Amplitude	-0.32682	-0.259494	-0.287883	-0.254443
Width	0.085	0.041663	0.036179	0.0270031
Asymmetry	= -0.45		0.278652	0.192566
Saturation	/	/	/	3.70758

- EGO model better fits SWIR absorptions and is sufficient to discriminate calcite from dolomite
- Estimated parameters might lose some meaning (width, saturation, asymmetry)

### Noise evolution

- Goal: Evaluate the radiance total noise and the signal dependent and independent components over years (AVIRIS - Lunar Lake - 1992 to 2009)




- The AGM total noise and noise components estimation procedure is applied on 5 AVIRIS images
- Total noise evolution: increasing SNR makes mineral identification easier
- For recent spectrometers, noise is not totally independent from signal
- Main noise sources and their impact:
  - Dark current  $\Rightarrow$  independent noise
  - Photon noise  $\Rightarrow$  dependent noise
- Estimation depends on the radiance of the image (high radiance implies high photon noise)

### Mineral identification procedure

- Goal: Mineral identification from EGO model parameters

#### Database creation



#### Identification procedure [9]

- Each mineral is defined by a set of parameters  $(P_1, \dots, P_M)$  and an expert rule to ensure the meaning of the identification
- Identify the mineral by comparing database parameters to the estimated ones  $(A_1, \dots, A_M)$  under the following constraints:
 
$$P_i \neq P_j \neq P_M \text{ where } i \in (P_1, \dots, P_M)$$

$$P_i \in G(m_i, \sigma_i)$$
- The output gives an identification probability for each mineral (several minerals can have non negative probability)

## Future works

1. Validate EGO model for several minerals having different absorption shapes
2. Improve the automatic EGO model parameter estimation
3. Take into account new noise model for completeness
4. Create database and associated expert rules
  - Adapt the procedure for mineral mixture
  - Develop expert rules for mineral characterization

[1] R. Marion and V. Carrère, Mineral Mapping Using the Automatized Gaussian Model (AGM) - Application to Two Industrial French Sites at Gardanne and Thann, Remote Sensing, 2018, 10, 146.  
 [2] L. Pompilio, G. Pedrazzi, M. Sgavetti, E. Cloutis, M. Craig, and T. Roush, Exponential Gaussian approach for spectral modeling: the EGO algorithm I. band saturation, Icarus, 2009.  
 [3] L. Pompilio, G. Pedrazzi, E. Cloutis, M. Craig, and T. Roush, Exponential gaussian approach for spectral modelling: the EGO algorithm II. band asymmetry, SIAM, 2005.  
 [4] N. Clark, Roger & L. Roush, Ed., Reflectance Spectroscopy: Quantitative Analysis Techniques for Remote Sensing Applications. Journal of Geophysical Research Atmospheres, 1984.  
 [5] N. Acito, M. Diani, and G. Corsini, Signal-dependent noise modeling and model parameter estimation in hyperspectral images. IEEE Transactions on Geoscience and Remote Sensing, 49(8):2957-2971, Aug 2011.  
 [6] J. M. Bioucas-Dias and J. M. P. Nascimento, Hyperspectral subspace identification. Model (AGM) - Application to Two Industrial French Sites at Gardanne and Thann, Remote Sensing, 2018, 10, 146.  
 [7] R. Du, W. Kibbe, S.M. Liu, Improved peak detection in mass spectrum by incorporating continuous wavelet transform-based pattern matching, Bioinformatics, 2006.  
 [8] A. Tarantola, Inverse Problem Theory and Model Parameter Estimation, SIAM, 2005.  
 [9] J.P. Poli and L. Boudet, A fuzzy expert system architecture for data and event stream processing. Fuzzy Sets and Systems, 2018, 343, p.20-34.  
 [10] R.N. Clark, G.A. Swayze, R.A. Wise, K.E. Live, T.M. Hoefen, R.F. Kokaly and S.J. Sutley, 2007, USGS Digital Spectral Library splib06a: U.S. Geological Survey Data Series 231  
 [11] N. Zain, F. Van der Meer, H. Van der Werff, Effect of Grain Size and Mineral Mixing on Carbonate Absorption Features in the SWIR and TIR Wavelength Regions. Remote Sensing, 2012; 4(4):987-1003.