



HAL
open science

Sequential Bayesian inversion of black-box functions in presence of uncertainties

Romain Ait Abdelmalek-Lomenech, Julien Bect, Emmanuel Vazquez

► **To cite this version:**

Romain Ait Abdelmalek-Lomenech, Julien Bect, Emmanuel Vazquez. Sequential Bayesian inversion of black-box functions in presence of uncertainties. MASCOT-NUM 2022, Jun 2022, Clermont-Ferrand, France. . ⟨hal-03694867⟩

HAL Id: hal-03694867

<https://centralesupelec.hal.science/hal-03694867v1>

Submitted on 14 Jun 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire HAL, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons CC BY-NC-ND 4.0 - Attribution - Non-commercial use - No Derivative Works - International License

SEQUENTIAL BAYESIAN INVERSION OF BLACK-BOX FUNCTIONS IN PRESENCE OF UNCERTAINTIES

Context & motivations

In engineering, many system design problems come down to finding design parameters for the system to operate under desired conditions. When time-consuming numerical simulations are used to assess the conditions of operation of such systems, it is essential to treat this problem—broadly known as "**inversion**"—using search methods that are very sparing in the number of simulations.

With this constraint in mind, we propose here a **sequential strategy** for a particular robust inversion problem that we call "**reliability-based inversion**" (**RBI**), in which the system has both **deterministic and uncertain inputs**. In this formulation, the objective is to retrieve the set of deterministic inputs such that the probability of the outputs exceeding a given level is greater than a threshold.


The reliability-based inversion (RBI) problem

We view our system as a **black-box function** $f : \mathbb{X} \times \mathbb{S} \mapsto \mathbb{R}$. In this setting, \mathbb{X} is the space of deterministic inputs and \mathbb{S} the space of **uncertain** inputs.

- Given a level $q \in \mathbb{R}$ and a threshold $\alpha \in]0, 1[$, **our objective is to approximate the set**

$$\Gamma(f) = \{x \in \mathbb{X} : \mathbb{P}(f(x, S) \geq q) \geq \alpha\}$$

where S is a random variable with **known distribution** \mathbb{P}_S on \mathbb{S} .



- Equivalently, we can formulate this problem as a **classification problem**, in which we wish to **approximate the classifier**

$$c(x) = \begin{cases} 1 & \text{if } x \in \Gamma(f) \\ 0 & \text{otherwise} \end{cases}$$

The Stepwise Uncertainty Reduction (SUR) principle

SUR strategies are a subset of the Bayesian strategies in which the points of evaluation are sequentially chosen by minimizing the expected future uncertainty on the object of interest, using a probabilistic surrogate of the unknown function.

- Consider $\xi \sim GP(\mu, k)$ a **Gaussian Process prior** on f , with μ and k respectively the mean and covariance functions of the process.
- We define the **current information** \mathcal{I}_n :

$$\mathcal{I}_n = \{(X_1, S_1, \xi(X_1, S_1)), \dots, (X_n, S_n, \xi(X_n, S_n))\}$$

- A SUR strategy choose the point **minimizing the expected future uncertainty**:

$$(X_{n+1}, S_{n+1}) \in \arg \min_{(x,s) \in \mathbb{X} \times \mathbb{S}} \mathbb{E}_n(U_{n+1} | X_{n+1} = x, S_{n+1} = s)$$

where:

- U_{n+1} is an uncertainty metric on the object of interest, depending on \mathcal{I}_{n+1}
- \mathbb{E}_n expectation with respect to \mathbb{P}_n , the distribution of ξ given \mathcal{I}_n

SUR approaches have been successfully used for the resolution of several problems regarding expensive-to-evaluate black box, including optimization [VW09; MTZ78], function fitting, and more standard inversion problems. [Bec+12]

Construction of a SUR criterion for the RBI problem

- Let us define the **integrated process** τ and $\Gamma(\xi)$ the associated **random excursion set** above the threshold α :

$$\tau(\xi, x) = \int_{\mathbb{S}} \mathbb{1}(\xi(x, s) \geq q) \mathbb{P}_S(ds) \quad \text{and} \quad \Gamma(\xi) = \{x \in \mathbb{X}, \tau(\xi, x) \geq \alpha\}$$

- We consider the uncertainty metric U_n defined by

$$U_n = \int_{\mathbb{X}} \tilde{p}_n(x)(1 - \tilde{p}_n(x)) dx$$

with $\tilde{p}_n(x) = \mathbb{P}_n(\tau(\xi, x) \geq \alpha)$

The link between the metric and the **uncertainty of the random set** $\Gamma(\xi)$ can be seen more clearly by remarking that:

$$U_n = \int_{\mathbb{X}} \mathbb{V}_n(\mathbb{1}(x \in \Gamma(\xi))) dx$$

with \mathbb{V}_n the conditional variance given \mathcal{I}_n


- The conditional distributions of $\tau(\xi, x)$ are **intractable**: the SUR criterion does not admit an analytic expression.
- Monte Carlo simulations**: ξ being Gaussian, we can generate ξ_1, \dots, ξ_M sample paths of ξ under \mathbb{P}_n

$$\frac{1}{M} \sum_{m=1}^M \mathbb{1}(\tau(\xi_m, x) \geq \alpha) \xrightarrow[M \rightarrow +\infty]{a.s.} \mathbb{P}_n(\tau(\xi, x) \geq \alpha) = \tilde{p}_n(x)$$

For each candidate point (x, s) , the sample paths are **reconditioned** according to values sampled from the distribution of $\xi(x, s)$ given \mathcal{I}_n

Numerical results

We compare, iteration by iteration, the proportion of misclassified points obtained with our method to the ones of methods focusing on the excursion set in the joint space $\mathbb{X} \times \mathbb{S}$ of design and uncertainties: the **straddle criterion** [Bry+05] and a **SUR approach** to standard inversion problems. [Bec+12]



Empirical evidences show that our method **generally outperforms** state of the art joint space inversion methods. Moreover, in all the test cases, the new SUR strategy never lags behind the others approaches considered.

References

- [Bec+12] J. Bect et al. "Sequential design of computer experiments for the estimation of a probability of failure". In: *Statistics and Computing* 22.3 (2012), pp. 773–793.
- [Bry+05] B. Bryan et al. "Active Learning for Identifying Function Threshold Boundaries". In: *Proceedings of the 18th International Conference on Neural Information Processing Systems*. NIPS'05. 2005.
- [MTZ78] J. Mockus, V. Tiesis, and A. Zilinskas. "The Application of Bayesian Methods for Seeking the Extremum". In: *Towards Global Optimization* 2.117–129 (1978), p. 2.
- [VW09] J. Villemonteix, E. Vazquez, and E. Walter. "An Informational Approach to the Global Optimization of Expensive-to-Evaluate Functions". In: *J. of Global Optimization* 44.4 (Aug. 2009), pp. 509–534.